

WALK THROUGH METAL DETECTOR – MODEL: UBG600

6/12/18 ZONES



TECHNICAL SPECIFICATION:

Power Supply:	AC85V – 264V
Working temperature:	-20°C – +50°C
Working Frequency:	4KHZ–8KHZ
Standard External size:	2200mm (H) x 800mm(W) x 580mm (D)
Standard Internal size:	2010mm (H) x 700mm (W)x 500mm (D)
Package size for door panels:	2260*650*260mm * 1 ctn
Package size for control unit:	780*390*250 mm* 1 ctn
Gross weight:	70KG



CHARACTERISTICS:

- Six mutual over-lapping detecting zones, simultaneous alarm from multi-zones.
- Sensitivity adjustment: Each zone has 100 sensitivity levels.
- Sound & LED alarm: Double sided LED indicator, easily shows where metal is.
- Automatically counts passengers and alarm times.
- Alarm strength indicator on control panel.
- Password protection, only an authorised person can operate.
- 4-8 hours backup battery (optional).
- Easy assembly: designed with only 2 cables and 8 screws, simple-to-follow instructions.
- Harmless to a human body: Harmless with heart pacemaker, pregnant women, magnetic floppy discs, recording tapes, etc.
- High density fireproof material.
- Self-diagnostic program when powered on, no need for initial or periodic calibration.
- Modular design, easy for maintenance and replacement parts.
- Sensitivity Test Piece: One yuan Coin, omnidirectional detection.



APPLICATION:

Exhibition Centers, Electronic Factories, Banks, Prisons, Government Offices, Hotels etc.

BoomGate Systems (PTY) LTD
Reg No. 98/23505/07 Engineering Access Control



www.boomgatesystems.co.za

WALK THROUGH METAL DETECTOR – MODEL: UBG5700

6/8/12/16/18/ 24 ZONES



TECHNICAL SPECIFICATION:

Power Supply:	AC85V – 264V
Working temperature:	-20°C – +50°C
Working Frequency:	4KHZ–8KHZ
Standard External size:	2200mm (H) x 800mm(W) x 580mm (D)
Standard Internal size:	2010mm (H) x 700mm (W)x 500mm (D)
Package size for door panels:	2260*650*260mm *1ctn
Package size for control unit:	780*390*250 mm*1ctn
Gross weight:	70KG



CHARACTERISTICS:

- Six mutual over-lapping detecting zones, simultaneous alarm from multi-zones.
- Sensitivity adjustment: Each zone has 256 sensitivity levels, 0 - 255 adjustable.
- 5.7 inch LCD screen.
- Infrared remote control.
- Sound & LED alarm: Double sided LED indicator, easily shows where metal is.
- Automatically counts passengers and alarm times.
- Alarm strength indicator on control panel.
- Password protection, only an authorised person can operate.
- Easy assembly: designed with only 2 cables and 8 screws, simple-to-follow instructions.
- Harmless to a human body: Harmless to pacemakers, pregnant women, magnetic floppy discs, recording tapes, etc.
- Using high density fireproof material.
- Self-diagnostic programme when power on, no need initial or periodic calibration.
- Modular design, easy for maintenance and replacement parts.
- Sensitivity Test Piece: One yuan Coin, omnidirectional detection.
- 4-8 hours backup battery (optional).



APPLICATION:

Exhibition Centers, Electronic Factories, Banks, Prisons, Government Offices, Hotels etc.